

Rack height 24U - 50U

- Universal square holes, cage nuts included
- Dell, HP, IBM, Cisco compatible
- 50U, 44U, 36U, 30U, 24U
- 3000 lbs (13610 kgs) capacity
- Meets EIA, 19" standards

Optimizes cooling and makes wiring easy

- Vertical cable organizer (sold separately with 50U)
- Streamlined support for power strips, PDUs

Designed for data centers

- 24" width is perfect for data centers
- Flush floor mount spreads load on floor tiles
- Optional side & filler panels
- Optional top panel with cable pass-throughs

Rack accessories

- Rack tops, caster kits, side panels & power strips may be purchased separately.



Open Frame Rack provides users with a versatile, customizable solution engineered to meet a diverse set of rack mounting needs. Ranging in heights from 24U to 50U, this rack optimizes cooling and promotes easy wiring, making it ideal for high density installations.

It is perfect for data center deployment. It includes a vertical cable organizer (sold separately with 50U), as well as support for power strips, PDUs and for APC tool-less mounting.

This rack features square holes, works perfectly with tool-less rails, and it's quick and easy to assemble.

The Open Frame Rack is compatible with 19" equipment developed by all of the leading OEMs including: Dell, HP, IBM, and Super Micro.

The Open Frame Server Rack also features a number of new design attributes built specifically for data center deployment.

The bottom of the open case has flush floor mounts that spread the rack's payload evenly over the floor.

It can also be ordered with optional side and top panels. The top panel comes with or without holes for cable pass-through