

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD

NOTES:

ELECTRICAL:


- VOLTAGE RATING: 125 VAC RMS.
- CURRENT RATING: 1.5 AMP.
- CONTACT RESISTANCE: 100 MILLIOHMS MAX.
- INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
- DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN.

CONFORM TO TIA/EIA 568 B.2-1

MATES WITH MODULAR PLUG CONFORMING TO FCC PART68.

MECHANICAL:

- HOUSING MATERIAL: PBT+30%GF UL 94V-0;COLOR:BLACK
- PANEL FRAME: CARBON STEEL, POWDER COATINGIN BLACK COLOR
- IDC MATERIAL: PC UL 94V-0, CONTACT: PHOSPHOR BRONZE WITH NICK PATING
- PART NUMBER: LUP6U-64103



COLOR CODING INFORMATION			
T568B		T568A	
PIN 8	BROWN	PIN 8	BROWN
PIN 7	BROWN/WHITE	PIN 7	BROWN/WHITE
PIN 6	GREEN	PIN 6	ORANGE
PIN 3	GREEN/WHITE	PIN 3	ORANGE/WHITE
PIN 2	ORANGE	PIN 2	GREEN
PIN 1	ORANGE/WHITE	PIN 1	GREEN/WHITE
PIN 4	BLUE	PIN 4	BLUE
PIN 5	BLUE/WHITE	PIN 5	BLUE/WHITE

DETACHED LISTS	MM (INCH)		DFTO SCC	DATE 01/14/09
	TOLERANCES EXCEPT AS NOTED		CHKD	DATE
			MFO	DATE
			APPVL	DATE
			MATERIAL : SEE NOTE	
	ANGLES ±		QT'Y :	
THIRD ANGLE PROJECTION		FINISH :		
		SCALE : 1		

TITLE CAT.6 PATCH PANEL, 24 PORTS			
DRAWING NO. LUP6U-64103			SIZE A3
PART NO. SEE NOTE			REV 0
DO NOT SCALE DRAWING			SHEET X OF Y